

Preparation

Product Specifications

- **Static cling** is made from highly plasticized white vinyl film that does not require an adhesive to adhere to polished or smooth surfaces such as glass or mirrors.
- **Static cling** have a release liner on the back and do not require any special skills or tools to install.

Application & Removal Techniques

The following is a general recommendation on steps that can be taken to apply static cling vinyls. Many of the points highlighted have proven to supply trouble free performance after the application is undertaken.

Surface Preparation

For proper adhesion the surface must be clean and dry. This product will not adhere properly to grease, oil, or dirt.

Mild soaps or detergents warm water and soft cloth will clean the surface prior to application.

For best results an ammonia based window cleaner can be used on all glass surfaces

Clings may be applied to a variety of smooth polished surfaces such as glass, plastic, chrome, and high gloss smooth painted surfaces.

Note: Always test the cleaning product before applying it onto a painted surface.

Application Method

Step 1

- Prepare a wetting solution of two or three teaspoons of liquid household detergent in one quart of cold water. regular water will also work in a pinch however not as effectively.

Tools Required:

- Paper Towel
- Credit Card
- Waterbottle
- Cling



Step 2

- Remove the static cling from the liner and lay the material on a clean, flat surface with the side up which will be adhered to the surface.



Step 3

- Flood the application surface with wetting solution, (alternate method - wetting solution can be sprayed directly on the substrate).



Step 4

- Place the cling in contact with the application surface. The wetting solution will allow the decal to be slid across the application surface for positioning purposes.



Step 5

- Once the material is in position, roll the water out, working from the center of the decal to the edges. Use a credit card.



Step 6

- Use paper towels to blot any excess moisture. Rub the edges to ensure the clings have adhered properly.

REMOVAL This product can be easily and cleanly removed and reused. Cling needs to be stored on the board or the liner in a clean, dry environment.

Note: If you find that you still have bubbles slowly push them out with a again with the credit card



Conclusion!

Installing Cling graphics is a simple follow-the-steps process. Although it takes very little time, it is not something to rush. With a little concentration and patience you can easily install quality vinyl graphics.

Order Your Real Estate Signs Online @
www.nutrends.ca/realestate

Are you getting Noticed?



Nutrends
SIGNS & PRINTING 
604.929.1587 | NUTRENDS.CA